

Dial Reading Viscometer

our original now with electronic drive



The Worldwide
Standard Viscometer

Electronic Drive
means quiet,
reliable operation

2-Year Limited
Warranty

Easy-to-Select
Speeds

Analog display
- Shows % Torque
- Use Factor Finder
to convert reading
to centipoise

Simple-to-use,
easy setup

Available in explosion proof
U.L. Class 1, Group D locations
(w/o Electronic Drive)

Accuracy: $\pm 1.0\%$ of range

Repeatability: $\pm 0.2\%$

What's Included?

Instrument

6 spindles (RV/HA/HB) (p39)

or 4 spindles (LV) (p39)

Spindle Guard Leg*

Lab Stand (Model A)

Carrying Case

*Not applicable to HA or HB versions

Optional Accessories

Viscosity Standards (p44)

RV/HA/HB-1 Spindle (p39)

Quick Action Lab Stand (p3)

Temperature Bath (p27)

Small Sample Adapter (p32)

UL Adapter (p34)

Thermosel (p30)

Helipath Stand with T-bar Spindles (p36)

Spiral Adapter (p38)

DIN Adapter (p38)

Quick Connect/Extension Links (p43)

Vane Spindles (p37 & 42)

VISCOSITY
RANGE
cP(mPa·s)

SPEEDS

MODEL	Min.	Max.	RPM	Number of increments
LVT	1 [†]	2M	.3-60	8
RVT	100 ^{††}	8M	.5-100	10
HAT	200 ^{††}	16M	.5-100	10
HBT	800 ^{††}	64M	.5-100	10

[†] 1 cP achieved with UL Adapter accessory; 15 cP on LV with standard spindle

^{††} Minimum viscosity is achieved with optional RV/HA/HB-1 spindle.

M = 1 million cP = Centipoise; mPa·s = Millipascal/seconds



Easy Speed
Adjustment
and On/Off
Control